1350x100mm

28

Reflective Elastic Band

Product identification. These accessories have CE marking to demonstrate compliance with Regulation (EU) 2016/425 on Personal Protective Equipment (Category 1 and Annex I Health & Safety Requirements. Your information. Use in low visibility conditions.
Materials: Elastic 70% polyester, 23.0% latex, extra 70% nylon, 30% polyester, reflective yarn.
Directions for use: Fasten the jogging band with the hook and loop fastener. Should be positioned on the upper arm, above the elbow joint. Ensure the reflective side is visible to the front and back. SHOULD BE WORN TO ADVISE TAP VISIBILITY PROBLEMS WHEN ALL ASPECTS OF CART FIND BE EXPOSED TO ADVISE TAP VISIBILITY PROBLEMS WHEN ALL ASPECTS OF CART FIND BE EXPOSED TO ADVISE TAP VISIBILITY PROBLEMS WHEN ALL ASPECTS OF CART FIND BE EXPOSED
Care instructions: Wash at 30°C. Do not bleach. Do not iron. Do not dry clean. Do not tumble dry. Wash separately or inside out. Dry in a shaded place. Do not use if damaged.
Warning against improper use. This reflector is accessory for visibility.
Warning against misuse. Do not use for any purpose other than visibility. Do not use for other items. Factory which may reduce the protection. Visibility of reflective material will degrade with exposure and usage. A damaged reflective sheeting reduces signal or obscures and masks, crosses or overlaps the reflective sheeting. Reflective sheeting may be damaged by sharp objects, heat, hot, sunburnt, abrasion, flexing, high UV radiation, temperature variations, humidity, rain, water, chemicals, solvents, cleaning agents, oil, grease, dirt, mud, or other substances. Reflective sheeting may be damaged by the effects of the product such as printing of tapes may compromise the retroreflective properties of the product. The product should not be used in places where its use flags could be mistaken for signals.
Storage: Store in clean, dry conditions. Do not store in places subjected to direct strong sunlight.
Disposal: Dispose of in accordance with local laws. Do not burn.
Disposal: Dispose of as normal household waste, please check your local disposal regulations.
Transport Packaging: Sealed and packed into cartons.

Reflectieband elastiek

Productidentificatie. Deze tillebeld en hersyset voor CE-markering, voor naleving overeenkomstig of Verordening (EU) 2016/425 Persoonlijk beschermende kleding Categorie 1 & Bijlag I Gezondheid- en veiligheidseisen.
Bugerrichtlinien Brug: verplichtend voor alle gebruikers.
Materialen: Elastiek 70% polyester, 23.0% latex, extra 70% nylon, 30% polyester, reflectieve garen.
Gebruiksaanwijzing. Sluit jogbandjes van hook-and-loop-fastener. Dit moet ook worden gedragen op de bovenarm, ongeveer 2 cm onder de bicepsspier. Zorg ervoor dat de reflectiezone zichtbaar is voor de achterkant en voorkant van de arm. Zo ook, ook bij hogere dan of zeven en gemiddelt 100 BEKE of 10 GEMIDDELDE BEKE DIENT DE REFLECTIEZONE TOTALE OPPERVLAKTE VAN MINIMAAL 200 VIERKANTE CENTIMETER TE ZIJN. DE REFLECTIEZONE DIENT TE ZIJN GEPLAATST OP DE BOVENARM, TUSSEN DE ELLEBOOG EN DE SCHOUDER, EN DIENT ZICHTBAAR TE ZIJN VOOR DE BESTUURDER. Reflectiezone moet zichtbaar zijn voor de bestuurder van de voertuig